

The listing of claims presented below replaces all prior versions and listings of claims in the application.

Listing of Claims

1. (Currently amended) A process for preparing fatty acid alkyl esters suitable for use as biodiesel from a starting material of fatty acid glycerides selected from the group consisting of vegetable oils, ~~edible or non-edible oils containing high free fatty acids~~, animal oils, fats and, fatty acids and a mixture thereof wherein esterification of the fatty acid and transesterification of triglycerides is carried out simultaneously, said process comprises the steps of:

- a) reacting fatty acid glycerides and fatty acid present in it with an alcohol having 1-4 carbon atoms at a temperature ranging between 70-300°C, pressure in a range of 1-30 bar, wherein the molar ratio of alcohol to fatty acid glycerides ranges from 3:1 to 30:1, in presence of a organometallic catalytic compound of tin wherein the compound is dioctyltinoxide wherein the concentration of catalyst is in a range of 0.01 to 3 weight percent of the fatty acid glycerides;
- b) obtaining fatty acid alkyl esters with glycerol;
- c) separating the glycerol from the fatty acid alkyl ester as immiscible phase by decantation;
- d) recovering and recycling the alcohol that is in excess by evaporation or distillation;
- e) purifying the fatty acid alkyl esters by washing with water, and
- f) purifying the washed ester obtained in step e) by distillation or treatment with a basic adsorbent selected from the group consisting of bauxite, clay, alumina, silica-alumina or a

combination thereof.

2. (Previously presented) The process as claimed in claim 1, wherein fatty acid glycerides are selected from the group consisting of vegetable oil, animal oil, fatty acids and a mixture thereof.

3. (Cancel)

4. (Cancel)

5. (Cancel)

6. (Previously presented) The process as claimed in claim 1, wherein the temperature of the reaction is in the range of 150-200°C.

7. (Previously presented) The process as claim 1, wherein the treatment with the adsorbent is carried out at 20-60°C.

8. (Cancel)

9. (Previously presented) The process as claimed in claim 1, wherein the biodiesel obtained has an acid value in a range of 0.01-0.50 mg KOH/g.

10. (Previously presented) The process as claimed in claim 1, wherein the biodiesel obtained has viscosity in a range of 4-7 cSt at 40°C.

11. (Previously presented) The process as claimed in claim 1, wherein the fatty acid alkyl esters produced are suitable for use as fuel in diesel engines, blending component for petrodiesel and as additive in petrofuel for enhancing lubricity, cetane number and biodegradability.

12. (Cancel)